



□ : 可客製化，請聯絡詢問
 ■ : 可快速調整

*可以客製化規格

TYPE	D1	d3(min)	L(= l)	W1(Max)	W2(Max)	Poles	Rated Torque	rated speed	Voltage	cooling
	mm	mm	mm	mm	mm		Nm	rpm	V	
PM45	45.3	16.8	10	7	4	10	0.28	5500	220	nature air cooling
PM56	56.3	(19)	6	9	7	14	0.08	3500	15VDC	
			12				0.17	3500		
PM58	58.3	19.3	15	7	5.5	10	0.77	5000	220	
			25				0.98	5000	220	
			35				1.32	5000	220	
PM68	68.3	22.7	23	7	5.5	14	0.64	3000	48VDC	
PM90	90	35.8	15	7.5	5.5	20	0.9	4500	220	
			26			20	1.6	3600	220	
PM120	120.3	42.7	30	9	6.5	20	3.18	3000	48VDC	





TYPE	D1	D3(min)	L(= l)	W1(Max)	W2(Max)	Poles	Rated Torque	rated speed	Voltage	cooling	
	mm	mm	mm	mm	mm		Nm	rpm	V		
TM140	140	(60)	30	18	18	22	42	700	220	water cooling	
TM175	175	(90)	50	22	22	22	55	500	200		
TM175			30	12	12		45	220	200		
TM210	210	(140)	70	17	15	40	140	150	220		
			100				222	150	220		
			60	16	12		40	125	250		600VDC
			60	16	12		40	60	200		220
TM290	290	(200)	50	24	18	40	193	170	300VDC		
			100	24	16		193	170	600VDC		
		(220)	60	17	13	60	200	80	220		
			110				584	60	600VDC		
TM360	360	(265)	50	29	28	60	394	150	220		
			70			60	571	70	220		
TM452	452	(340)	150	37	22	80	1830	40	220		
			160	17	13		1909	60	220		
TM530	530	(420)	100	29	28	80	2134	55	600VDC		

